



Validation Help

EFILive Support - 2020-11-06 - Comments (0) - Store, Sales and Shipping

VIN License Validation

For VIN License purchases, you must be running EFILive V8.2.24 software or later to generate valid VIN License Auth Codes.

1. Generate valid [Serial Number and Auth Code](#) details from EFILive V8 Scan and Tune software.
2. FlashScan/AutoCal Serial numbers must be entered into the Serial field. The Serial must be either 10 or 12 characters.
3. FlashScan/AutoCal Authentication code must be entered into the Auth Code field. The auth code must be exactly 20 characters.
4. Enter the Qty to purchase.
5. Select [Check Serial & Code].



AutoCal V3 VIN License

AutoCal customers may purchase additional VIN licenses to tune additional controllers. AutoCal is pre-configured with a maximum VIN license slot capacity of one and ships with one VIN license. Tuners can increase the maximum VIN slot limit capacity so additional VIN licenses may be purchased and activated. The maximum VIN slot limit and VIN license limit is 600 per AutoCal device.

US\$125.00

Availability: In stock

Serial Number *

006000000144

Maximum 12 characters (0 remaining)

Auth Code *

HXGXJE-ZBHAHM-WHR2AK

Maximum 20 characters (0 remaining)

- 1 +

CHECK SERIAL & CODE

SUBTOTAL: US\$125.00

6. Add validated code to cart



AutoCal V3 VIN License

AutoCal customers may purchase additional VIN licenses to tune additional controllers. AutoCal is pre-configured with a maximum VIN license slot capacity of one and ships with one VIN license.

Tuners can increase the maximum VIN slot limit capacity so additional VIN licenses may be purchased and activated. The maximum VIN slot limit and VIN license limit is 600 per AutoCal device.

US\$125.00

Availability: In stock

Serial Number *

Maximum 12 characters (0 remaining)

Auth Code *

Maximum 20 characters (0 remaining)

-

1

+

ADD TO CART

SUBTOTAL: US\$125.00

- If the serial and auth code do not pass validation, an error code will be displayed. Refer to the [Validation Error Codes](#) list for details. Customers should ensure that the information entered is EXACTLY as displayed in EFILive software.



AutoCal V3 VIN License

AutoCal customers may purchase additional VIN licenses to tune additional controllers. AutoCal is pre-configured with a maximum VIN license slot capacity of one and ships with one VIN license.

Tuners can increase the maximum VIN slot limit capacity so additional VIN licenses may be purchased and activated. The maximum VIN slot limit and VIN license limit is 600 per AutoCal device.

US\$125.00

Availability: In stock

Serial Number *

Maximum 12 characters (0 remaining)

Auth Code *

Maximum 20 characters (0 remaining)

Error \$1008: 4 license(s) cannot be added to this device as it exceeds the configured maximum of 5 VIN licenses. A maximum of 1 licenses can be ordered.

-

4

+

CHECK SERIAL & CODE

SUBTOTAL: US\$500.00

- Check you are ordering the correct product - the EFILive store validation works on SKU.
- Check software version used to generate the auth code.
- Check for spaces at the start/end of code.
- Hyphens are essential.
- Serial must be either 10 or 12 characters.
- Auth Code must be exactly 20 characters.
- Verify quantity limit has not been exceeded.

Tuning Option Validation

1. Enter FlashScan Serial number into the Serial field. The Serial must be either 10 or 12 characters.
2. Set the Qty field to 1.
3. Select [Check Serial & Code].
4. Add validated code to cart.
5. If code does not pass validation, ensure that the code is EXACTLY as displaying in EFILive software.
 1. Check you are ordering the correct product - the EFILive store validation works on SKU.
 2. Check for spaces at the start/end of code.
 3. Code must be either 10 or 12 characters.

Controller Authorization Code Validation

1. You must obtain your controller authorization code. ([How?](#)).
2. Enter the controller authorization code into the Auth Code field. Ensure that the code is EXACTLY as displaying in EFILive software. Hyphens are essential, and the code must be exactly 29 characters.
3. Set the Qty field to 1.
4. Select [Check Serial & Code].
5. Add validated code to cart.
6. If code does not pass validation, ensure that the code is EXACTLY as displaying in EFILive software.
 1. Check for spaces at the start/end of code.
 2. Hyphens are essential.
 3. Code must be exactly 29 characters.

V1 PCM License Validation

1. Generate valid [Serial Number and Auth Code](#) details from V7.5 Tune Tool software.
2. Enter the FlashScan V1 Serial number into the Serial field. Serial must be either 10 or 12 characters.
3. Enter the Auth Code into the Auth Code field. The auth code must be exactly 17 characters.
4. Enter the Qty to purchase.
5. Select [Check Serial & Code].
6. Add validated code to cart.
7. If code does not pass validation, an error code will be displayed. Refer to the [Validation Error Codes](#) list for details. Customers should ensure that the information entered is EXACTLY as displayed in EFILive software.
 1. Check for spaces at the start/end of code.
 2. Hyphens are essential.
 3. Serial must be either 10 or 12 characters.

4. Auth Code must be exactly 17 characters.
5. Verify quantity limit has not been exceeded.

Related Content

- [Serial Number and Auth Codes](#)
- [Validation Error Codes](#)